

# WOOD STOVES

**COLORATO**

www.colorato.net

Model	CLWS-07G	CLWS-08G	CLWS-09SSD	CLWS-09CSD	CLWS-120V
Characteristics	Steel top plate and steel door	Steel top plate and steel door	Steel top plate and steel door	Cast iron top plate and cast iron door	Steel top plate and steel door With oven
Power (kW)	7	8	9	9	12
Efficiency grade (wood fuel)	63%	76,5%	65%	65%	69%
METAL THICKNESS (mm)	Upper plate	4	4	-	4
	Doors	3	3	-	3
	Sides	2	2	2	2
Dimensions (mm)	W 330 L 360 H 930	W 465 L 390 H 790	W 490 L 450 H 930	W 490 L 450 H 930	W 510 L 480 H 1060
Dimensions of entrance of burning space (mm)	W 190 H 200	W 330 H 240	W 265 H 225	W 265 H 225	W 385 H 225
Dimensions of wood storage space (mm)	W 305 L 275 H 275	W 430 L 325 H 180	W 400 L 385 H 300	W 400 L 385 H 300	W 490 L 440 H 220
Pipe	ø120	ø120	ø120	ø120	ø120
Weight (kg)	39	54	55	66	98
Oven dimensions (mm)	-	-	-	-	W 435 L 300 H 230
Material of the internal of the burning space	Schamotte brick	Schamotte brick	Schamotte brick	Schamotte brick	Schamotte brick
Heating area (m <sup>2</sup> )	25-35	35-40	50-60	50-60	70-80
Certificates	CE	CE	CE	CE	CE
Available colors	BLACK	BLACK	BLACK/RED	BLACK/RED	BLACK/RED


**CLWS-07G**

**CLWS-08G**

**CLWS-09SSD**
**CLWS-09CSD**

**CLWS-120V**

**30%**  
ECONOMY

## PIPE EXCHANGER

Saving more than 30% of the heating that is being emitted through the pipe of the stove. This specific exchanger can be adjusted to all the models of the stoves.

Dimension: 300x200x1000 mm  
Diameter of the main pipe: ø 120 mm

